

radiating antenna (1) and multiple thermocouples (6,6',6"), the radiating antenna being submerged within a fluid flow, characterized in that

18
said radiating antenna (1) [is] adapted to be submerged within a flow which proceeds through a central channel (2) surrounding said radiating antenna (1) towards the distal end of said catheter and passes from said catheter through a first opening (3) into a bladder to be treated, while flowing back into said catheter towards [the] a proximal end thereof through a second separate opening (4) of a side channel (5) surrounding [the] power supply cables of said thermocouples (6,6',6"),

[the] ends of said thermocouples (6,6',6") are adapted to project out of said second opening (4), being thus deflected outwards into the bladder when said balloon (7) is inflated by injecting a fluid through a second side channel (8) and third opening (9), whereby [the] outwardly deflected ends of said thermocouples (6,6',6") are adapted to come into tangential engagement with a bladder wall (32) irradiated by said antenna (1).

2. A radiating device including a catheter provided at its distal end with an inflatable balloon and adapted to receive multiple injected liquid fluid flows passing therethrough, a radiofrequency radiating antenna and multiple thermocouples, the radiating antenna being submerged within a fluid flow, characterized in that

said radiating antenna is adapted to be submerged within a flow which proceeds through a central channel surrounding said radiating antenna towards a distal end of said catheter and passes from said catheter through a first opening into an organ to be treated, while flowing back into said catheter towards a proximal end thereof through a second

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, D. C. 20005
202-408-4000

separate opening of a side channel surrounding power supply cables of said thermocouples.

ends of said thermocouples are adapted to project out of said second opening, being thus deflected outwards into the organ when said balloon is inflated by injecting a fluid through a second side channel and third opening, whereby the outwardly deflected ends of said thermocouples are adapted to come into tangential engagement with a wall of the organ irradiated by said antenna.

3. A radiating device including a catheter provided at its distal end with an inflatable balloon and adapted to receive multiple injected liquid fluid flows passing therethrough, a radiofrequency radiating antenna and multiple thermocouples, the radiating antenna being submerged within a fluid flow, characterized in that

said radiating antenna is adapted to be submerged within a flow which proceeds through a central channel surrounding said radiating antenna towards a distal end of said catheter and passes from said catheter through a first opening into an organ to be treated, while flowing back into said catheter towards a proximal end thereof through a second separate opening of a side channel surrounding power supply cables of said thermocouples.

ends of said thermocouples are adapted to project out of said second opening, being thus deflected outwards into the organ when said balloon is inflated by injecting a fluid through a second side channel and third opening, whereby outwardly deflected ends of said thermocouples are adapted to come into engagement with a wall of the organ irradiated by said antenna.

4. A radiating device for irradiating an organ comprising:

a catheter provided with an inflatable balloon and including a central channel, first and second side channels, and first, second, and third openings;

an antenna, situated at a first end portion of the catheter, the antenna adapted for being submerged in a first fluid that flows through the central channel surrounding the antenna towards the first end portion of the catheter, passes from the catheter through the first opening, and flows back into the catheter towards a second end portion thereof through the second opening; and

a plurality of thermocouples, having ends, the plurality of thermocouples extending along the first side channel of the catheter, each of the ends of the plurality of thermocouples adapted to project out of the second opening and to be deflected outwards when the balloon is inflated by injecting a second fluid through the second side channel and the third opening.

wherein the deflected ends of the plurality of thermocouples adapted to contact a wall of the organ irradiated by the antenna.

5. A radiating device for irradiating an organ comprising:

a catheter provided with an inflatable balloon and including first and second channels and a first opening;

an antenna, situated at an end portion of the catheter, the antenna adapted for being submerged in a fluid that flows through the first channel surrounding the antenna and into the organ; and

a plurality of thermocouples, having ends, the plurality of thermocouples
extending along the second channel, each of the ends of the plurality of thermocouples
projecting out of the first opening and being deflected outwards when the balloon is
inflated,

wherein the deflected ends of the plurality of thermocouples are adapted to
contact a wall of the hollow organ irradiated by the antenna.

6. A radiating device for irradiating an organ comprising:

a catheter provided with an inflatable balloon;

an antenna, situated at an end portion of the catheter, adapted for irradiating the
organ;

a channel for providing a fluid to the organ; and

a plurality of thermocouples, having ends, the plurality of thermocouples
extending along the catheter, each of the ends of the plurality of thermocouples being
deflected outwards when the balloon is inflated,

wherein the deflected ends of the plurality of thermocouples are adapted to
contact a wall of the organ irradiated by the antenna.

7. A radiating device for irradiating an organ comprising:

a catheter provided with an inflatable balloon and including first and second
channels and a first opening;

an antenna, situated at an end portion of the catheter, the antenna adapted for being submerged in a fluid that flows through the first channel surrounding the antenna and into the organ; and

a plurality of temperature sensing devices, having ends, the plurality of temperature sensing devices extending along the catheter, each of the ends of the plurality of temperature sensing devices being deflected outwards when the balloon is inflated, wherein the deflected ends of the plurality of temperature sensing devices are adapted to contact a wall of the organ irradiated by the antenna.

8. A radiating device for irradiating an organ comprising:

a catheter provided with an inflatable balloon;

an antenna, situated at an end portion of the catheter, for irradiating the organ;

a channel for providing a fluid to the organ; and

a plurality of temperature sensing devices, having ends, the plurality of temperature sensing devices extending along the catheter, each of the ends of the plurality of temperature sensing devices being deflected outwards when the balloon is inflated,

wherein the deflected ends of the plurality of temperature sensing devices are adapted to contact a wall of the organ irradiated by the antenna.

9. A radiating device for irradiating an organ comprising:

a catheter;

an antenna, situated at an end portion of the catheter, adapted for irradiating the organ;

organ;

a channel, within the catheter, adapted for providing a fluid comprising a cytotoxic substance to the organ; and

a plurality of temperature sensing devices, having ends, the plurality of temperature sensing devices extending along the catheter, each of the ends of the plurality of temperature sensing devices adapted for being deflected outwards after the catheter is inserted into the organ,

wherein the deflected ends of the plurality of temperature sensing devices are adapted to contact a wall of the organ irradiated by the antenna.

10. A radiating device for irradiating an organ comprising:

a catheter, including a channel adapted for providing a fluid to the organ;

an antenna, situated at an end portion of the catheter, adapted for irradiating the organ; and

a plurality of temperature sensing devices, having ends, the plurality of temperature sensing devices extending along the catheter, each of the ends of the plurality of temperature sensing devices being deflected outwards after the catheter is inserted into the organ,

wherein the deflected ends of the plurality of temperature sensing devices are adapted to contact a wall of the organ irradiated by the antenna.

11. A radiating device for irradiating a cavity comprising:

a catheter;

an antenna, situated at an end portion of the catheter, for irradiating the cavity;

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, D.C. 20005
202-408-4000

23

a channel extending along the catheter and adapted for providing fluid to the cavity; and

a plurality of temperature sensing devices, having ends, the plurality of temperature sensing devices extending along the catheter, each of the ends of the plurality of temperature sensing devices being deflected outwards after the catheter is inserted into the cavity,

wherein the deflected ends of the plurality of temperature sensing devices are adapted to contact a wall of the cavity irradiated by the antenna.

14. The radiating device as recited in claim 13, adapted for fluid flow by the antenna and into the cavity.

16. The radiating device as recited in claim 15, adapted for fluid flow by the shielded cable and the antenna and into the cavity.

18. The radiating device as recited in claim 11, adapted for flow of a conditioning liquid.

19. The radiating device as recited in claim 11, adapted for flow of a solution of a selective cytotoxicity substance.

20. The radiating device as recited in claim 11, wherein the antenna is adapted for a frequency range of 900-1000 MHZ.